# PRT RED M S

Perrot spojka, redukcija, ženski dio na muškom dijelu

## Karakteristike

| | |
|---|---|
| **Priključak 1** | Ženski dio spojke |
| **Oblik brtve 1** | O prsten, brtveni |
| **Priključak 2** | Muški dio spojke |
| **Površinska zaštita** | vruće pocinčana |



## Artikl

| Naziv | Radni tlak (bar) | Dimenzija spojke (mm) |
|---|---|---|
| **PRT RED M70-S50** | 12,0 | 70,0 / 50,0 |
| **PRT RED M89-S70** | 12,0 | 89,0 / 70,0 |
| **PRT RED M108-S70** | 12,0 | 108,0 / 70,0 |
| **PRT RED M108-S89** | 12,0 | 108,0 / 89,0 |
| **PRT RED M133-S89** | 12,0 | 133,0 / 89,0 |
| **PRT RED M133-S108** | 12,0 | 133,0 / 108,0 |
| **PRT RED M159-S108** | 12,0 | 159,0 / 108,0 |
| **PRT RED M159-S133** | 12,0 | 159,0 / 133,0 |
| **PRT RED M216-S159** | 12,0 | 216,0 / 159,0 |

*Usprkos pažljivoj provjeri ne mogu se isključiti pogreške i zbog toga ne preuzimamo odgovornost za sadržane podatke.*