

PRT S HR

Perrot spojka, muški dio, vanjski navoji

HANSA FLEX

Karakteristike

Priključak 1	Muški dio spojke
Priključak 2	BSP vanjski navoj, cilindrični
Materijal	Čelik
Površinska zaštita	vruće pocinčana



Artikli

Naziv	Radni tlak (bar)	Dimenzija spojke (mm)	G1
PRT S 50 HR 1.1/2	25,0	50,0	G 1,1/2" - 11
PRT S 50 HR 2	25,0	50,0	G 2" -11
PRT S 70 HR 2	25,0	70,0	G 2" -11
PRT S 70 HR 2.1/2	25,0	70,0	G 2,1/2" - 11
PRT S 70 HR 3	25,0	70,0	G 3" -11
PRT S 89 HR 2.1/2	25,0	89,0	G 2,1/2" - 11
PRT S 89 HR 3	25,0	89,0	G 3" -11
PRT S 108 HR 2.1/2	25,0	108,0	G 2,1/2" - 11
PRT S 108 HR 3	25,0	108,0	G 3" -11
PRT S 108 HR 4	25,0	108,0	G 4" -11
PRT S 133 HR 2.1/2	25,0	133,0	G 2,1/2" - 11
PRT S 133 HR 4	25,0	133,0	G 4" -11
PRT S 133 HR 5	25,0	133,0	G 5" -11
PRT S 159 HR 2.1/2	25,0	159,0	G 2,1/2" - 11
PRT S 159 HR 4	25,0	159,0	G 4" -11
PRT S 159 HR 6	25,0	159,0	G 6" -11