

Karakteristike

| | |
|--|---|
| Priključak | Priključci za ulje: A + B = G 1/2"; Ulje curenja straga = G 1/4" |
| Izvedba | Standardna varijanta Tip "CD" s visokotlačnim brtvljenjem two hole flange bolt circle 106.4 Vratilo Ø 25mm |
| Ulazni i povratni tlak s vodom za curenje ulja max. | 175 bar |



Artikli

| Naziv | Protok max. (L/min) | Volumen trošenja (cc) | Broj okretaja min. (rpm) | Broj okretaja max. (rpm) | Okretni moment max. (N-m) | Pad tlaka max. (bar) | Pmax. at 0-100 rpm (bar) | Pmax. at 100-300 rpm (bar) | Pmax. at 300-600 rpm (bar) | Pmax. at 600 rpm (bar) | L (mm) | Težina (kg) |
|----------------|------------------------|--------------------------|-----------------------------|-----------------------------|------------------------------|-------------------------|-----------------------------|-------------------------------|-------------------------------|---------------------------|-----------|----------------|
| HK EPRM 050 CD | 40 | 51,5 | 10 | 775 | 100 | 140 | 150 | 75 | 50 | 20 | 138 | 6,8 |
| HK EPRM 080 CD | 60 | 80,3 | 10 | 750 | 195 | 175 | 150 | 75 | 50 | 20 | 143 | 6,9 |
| HK EPRM 100 CD | 60 | 99,8 | 10 | 600 | 240 | 175 | 150 | 75 | 50 | - | 147 | 7,2 |
| HK EPRM 125 CD | 60 | 125,7 | 10 | 475 | 300 | 175 | 150 | 75 | 50 | - | 151 | 7,3 |
| HK EPRM 160 CD | 60 | 159,6 | 10 | 375 | 390 | 175 | 150 | 75 | 50 | - | 157 | 7,5 |
| HK EPRM 200 CD | 60 | 199,8 | 10 | 300 | 385 | 140 | 150 | 75 | - | - | 164 | 8,0 |
| HK EPRM 250 CD | 60 | 250,1 | 10 | 240 | 390 | 110 | 150 | 75 | - | - | 173 | 8,4 |
| HK EPRM 315 CD | 60 | 315,7 | 10 | 190 | 390 | 90 | 150 | 75 | - | - | 184 | 9,1 |
| HK EPRM 400 CD | 60 | 397,0 | 10 | 150 | 380 | 70 | 150 | 75 | - | - | 198 | 9,8 |

max. pressure on shaft seal (without leak oil line) or pressure in leak oil line – Vrijednosti za okretni moment i padove tlaka vrijede za trajni pogon – pmax = maks. tlak

Pribor

HK V0 590 Šok ventil

Rezervni dijelovi

HK EP DS Brtveni set za hidraulični planetarni motor