


Karakteristike

Radni tlak	do 250 bara
Brzina klizanja max.	0,5 m/s
Temperatura min.	-30 °C
Temperatura max.	110 °C
Mediji	Mineralna ulja Emulzije vode
Montaža	u zatvorenim ili otvorenim utorima
Materijal	(1) Brtva: NBR ojačan tkaninom (2) Potporni prsten: Acetal smola / PTBR



Spaltmaß / Clearance	
Druck / Pressure (bar)	e (mm)
160	< 0,2
250	< 0,1



Toleranz / Tolerance		
d	D	L
H8 / f7	H9	+0,2 0

Opis

jednostavno rješenje.

brtva koja se ne haba.

vrlo dobra učinkovitost brtvljenja kod niskog tlaka.

Artikli

Naziv	D (mm)	d (mm)	L (mm)
B 208 165-GS	53,00	42,00	10,00
B 267 236-P	68,00	60,00	11,00
B 275 216-GS	70,00	55,00	10,50
B 314 255-GS	80,00	65,00	11,50
B 334 255-GS	85,00	65,00	14,50
B 334 275-GS	85,00	70,00	12,00
B 366 307-GS	93,00	78,00	11,50
B 374 314-GS	95,00	80,00	12,00
B 748 669-GS	190,00	170,00	14,50