

FI ND E MA

Filtarski element za niskotlačni filter MA

HANSA FLEX


Karakteristike

Temperatura min. -25 °C

Temperatura max. 120 °C

Materijal Brtva: NBR

Radni tlak maks. 10 bar



Artikli

Naziv	Finoća filtra (µm)	Površina filtra (cm ²)	Qmax (L/min)	Filter material	L (mm)	Ø A (mm)	Ø B (mm)	Težina (kg)
FI ND E MA 0093 A03	3,0	590	15	anorganski	93,0	47,0	25,5	0,20
FI ND E MA 0030 P25	25,0	1824	80	organic	178,0	58,0	32,2	0,27
FI ND E MA 0025 M60	60,0	1575	150	žičano pletivo	142,0	83,2	47,5	0,52
FI ND E MA 0050 A03	3,0	4020	200	anorganski	249,0	78,5	40,3	0,72
FI ND E MA 0050 A06	6,0	4020	200	anorganski	249,0	78,5	40,3	0,72
FI ND E MA 0050 A10	10,0	4020	200	anorganski	249,0	78,5	40,3	0,72
FI ND E MA 0060 M100	100,0	4280	300	žičano pletivo	265,5	83,2	47,5	0,98
FI ND E MA 0040 M60	60,0	2000	330	žičano pletivo	210,0	140,0	51,0	0,79
FI ND E MA 0045 P03	3,0	10000	350	organic	221,5	152,0	88,0	0,60
FI ND E MA 0100 M40	40,0	6370	450	žičano pletivo	372,0	83,2	47,5	0,98
FI ND E MA 0100 M60	60,0	4410	450	žičano pletivo	372,0	83,2	47,5	1,42
FI ND E MA 0463 A03	3,0	10650	350	anorganski	463,0	106,0	72,0	0,95
FI ND E MA 0463 A06	6,0	10650	400	anorganski	463,0	106,0	72,0	0,95
FI ND E MA 0463 A10	10,0	10650	450	anorganski	463,0	106,0	72,0	0,95

Qmax - maks. volumenska struja – filter FI ND E MA 0050 *** za uređaj za filtriranje u sporednoj struji NSFA tip D – filter FI ND E MA 0463 *** za uređaj za filtriranje u sporednoj struji NSFA tip E

je rezervni dio uz sljedeće proizvode

NSFA Typ D Postrojenje za filtriranje u sporednoj struji, tip D

NSFA Typ E Postrojenje za filtriranje u sporednoj struji, tip E