K-BIMETALLTHERMOMETER 52-2

Bimetallic thermometers

HANSA FLEX

Karakteristike

Tip	52
Korekcija prikaza	Trimming pointer
Radni tlak	Max. 25 bar (on thermowell)
Odaberite i	Thermowell (removable) with locking screw
Uronjivo tijelo	Ø 8 mm, CrNi steel
Kućište, prsten	CrNi steel
Prozirna pločica	Flat instrument glass



Napomena

Drugi podatci na zahtjev.

Opis

Applications: Extremely versatile design for use in machine, vessel, pipeline and plant construction as well as for heating systems.

Artikl

Naziv	Područja prikaza	Ø (mm)	Duljina uronjivog tijela	Priključak
K- 07 20 07 26	-30 °C to +50 °C	63,0	thermowell L1 = 63mm, L2 = 43mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 27	0 °C to +120 °C	63,0	thermowell L1 = 63mm, L2 = 43mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 28	0 °C to +160 °C	63,0	thermowell L1 = 63mm, L2 = 43mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 29	0 °C to +200 °C	63,0	thermowell L1 = 63mm, L2 = 43mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 30	0 °C to +250 °C	63,0	thermowell L1 = 63mm, L2 = 43mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 31	-30 °C to +50 °C	63,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 32	0 °C to +120 °C	63,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 33	0 °C to +160 °C	63,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 34	0 °C to +200 °C	63,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 35	0 °C to +250 °C	63,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 36	-30 °C to +50 °C	63,0	thermowell L1 = 160mm, L2 = 140mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 37	0 °C to +120 °C	63,0	thermowell L1 = 160mm, L2 = 140mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 07 38	0 °C to +160 °C	63,0	thermowell L1 = 160mm, L2 = 140mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 11	-30 °C to +50 °C	100,0	thermowell L1 = 63mm, L2 = 43mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 12	0 °C to +120 °C	100,0	thermowell L1 = 63mm, L2 = 43mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 13	0 °C to +160 °C	100,0	thermowell L1 = 63mm, L2 = 43mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 14	0 °C to +250 °C	100,0	thermowell L1 = 63mm, L2 = 43mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 15	-30 °C to +50 °C	100,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 16	0 °C to +120 °C	100,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 17	0 °C to +160 °C	100,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 18	0 °C to +200 °C	100,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 19	0 °C to +250 °C	100,0	thermowell L1 = 100mm, L2 = 80mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 20	-30 °C to +50 °C	100,0	thermowell L1 = 160mm, L2 = 140mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 21	0 °C to +120 °C	100,0	thermowell L1 = 160mm, L2 = 140mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 22	0 °C to +160 °C	100,0	thermowell L1 = 160mm, L2 = 140mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 23	0 °C to +200 °C	100,0	thermowell L1 = 160mm, L2 = 140mm	Flush, with collar for thermowell, Ø 18 mm
K- 07 20 02 24	0 °C to +250 °C	100,0	thermowell L1 = 160mm, L2 = 140mm	Flush, with collar for thermowell, Ø 18 mm

Pribor

K-SCHUTZROHRE EINSCHRAUB	Screw-in thermowells
K-SCHUTZROHRE EINSCHWEISS	Weld-in thermowells

Usprkos pažljivoj provjeri ne mogu se isključiti pogreške i zbog toga ne preuzimamo odgovornost za sadržane podatke.