

# K-BIMETALLTHERMOMETER 52-2

Bimetallic thermometers

**HANSA FLEX**

## Karakteristike

|                   |   |
|-------------------|---|
| Tip               | 52  |
| Korekcija prikaza | Trimming pointer                          |
| Radni tlak        | Max. 25 bar (on thermowell)               |
| Odaberite i       | Thermowell (removable) with locking screw |
| Uronjivo tijelo   | Ø 8 mm, CrNi steel                        |
| Kućište, prsten   | CrNi steel                                |
| Prozirna pločica  | Flat instrument glass                     |



## Napomena

Drugi podatci na zahtjev.

## Opis

Applications: Extremely versatile design for use in machine, vessel, pipeline and plant construction as well as for heating systems.

## Artikli

| Naziv          | Područja prikaza | Ø (mm) | Duljina uronjivog tijela          | Priključak                                 |
|----------------|------------------|--------|-----------------------------------|--|
| K- 07 20 07 26 | -30 °C to +50 °C | 63,0   | thermowell L1 = 63mm, L2 = 43mm   | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 27 | 0 °C to +120 °C  | 63,0   | thermowell L1 = 63mm, L2 = 43mm   | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 28 | 0 °C to +160 °C  | 63,0   | thermowell L1 = 63mm, L2 = 43mm   | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 29 | 0 °C to +200 °C  | 63,0   | thermowell L1 = 63mm, L2 = 43mm   | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 30 | 0 °C to +250 °C  | 63,0   | thermowell L1 = 63mm, L2 = 43mm   | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 31 | -30 °C to +50 °C | 63,0   | thermowell L1 = 100mm, L2 = 80mm  | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 32 | 0 °C to +120 °C  | 63,0   | thermowell L1 = 100mm, L2 = 80mm  | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 33 | 0 °C to +160 °C  | 63,0   | thermowell L1 = 100mm, L2 = 80mm  | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 34 | 0 °C to +200 °C  | 63,0   | thermowell L1 = 100mm, L2 = 80mm  | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 35 | 0 °C to +250 °C  | 63,0   | thermowell L1 = 100mm, L2 = 80mm  | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 36 | -30 °C to +50 °C | 63,0   | thermowell L1 = 160mm, L2 = 140mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 37 | 0 °C to +120 °C  | 63,0   | thermowell L1 = 160mm, L2 = 140mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 07 38 | 0 °C to +160 °C  | 63,0   | thermowell L1 = 160mm, L2 = 140mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 11 | -30 °C to +50 °C | 100,0  | thermowell L1 = 63mm, L2 = 43mm   | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 12 | 0 °C to +120 °C  | 100,0  | thermowell L1 = 63mm, L2 = 43mm   | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 13 | 0 °C to +160 °C  | 100,0  | thermowell L1 = 63mm, L2 = 43mm   | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 14 | 0 °C to +250 °C  | 100,0  | thermowell L1 = 63mm, L2 = 43mm   | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 15 | -30 °C to +50 °C | 100,0  | thermowell L1 = 100mm, L2 = 80mm  | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 16 | 0 °C to +120 °C  | 100,0  | thermowell L1 = 100mm, L2 = 80mm  | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 17 | 0 °C to +160 °C  | 100,0  | thermowell L1 = 100mm, L2 = 80mm  | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 18 | 0 °C to +200 °C  | 100,0  | thermowell L1 = 100mm, L2 = 80mm  | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 19 | 0 °C to +250 °C  | 100,0  | thermowell L1 = 100mm, L2 = 80mm  | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 20 | -30 °C to +50 °C | 100,0  | thermowell L1 = 160mm, L2 = 140mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 21 | 0 °C to +120 °C  | 100,0  | thermowell L1 = 160mm, L2 = 140mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 22 | 0 °C to +160 °C  | 100,0  | thermowell L1 = 160mm, L2 = 140mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 23 | 0 °C to +200 °C  | 100,0  | thermowell L1 = 160mm, L2 = 140mm | Flush, with collar for thermowell, Ø 18 mm |
| K- 07 20 02 24 | 0 °C to +250 °C  | 100,0  | thermowell L1 = 160mm, L2 = 140mm | Flush, with collar for thermowell, Ø 18 mm |

## Pribor

|                           |                      |
|---------------------------|----------------------|
| K-SCHUTZROHRE EINSCHRAUB  | Screw-in thermowells |
| K-SCHUTZROHRE EINSCHWEISS | Weld-in thermowells  |