

# K-BIMETALLTHERMOMETER 52-1

Bimetallic thermometers

**HANSA FLEX**

## Karakteristike

Tip	52
Korekcija prikaza	Trimming pointer
Radni tlak	Max. 25 bar (on stem)
Uronjivo tijelo	Ø 8 mm, CrNi steel 1.4571
Kućište, prsten	CrNi steel
Prozirna pločica	Flat instrument glass



## Napomena

Drugi podatci na zahtjev.

## Opis

Applications: Versatile design for use in industrial applications.

## Artikli

Naziv	Područja prikaza	Ø (mm)	Duljina uronjivog tijela	Navoj
K- 07 20 02 72	-30 °C to +50 °C	100,0	63 mm	G 1/2
K- 07 20 02 73	0 °C to +120 °C	100,0	63 mm	G 1/2
K- 07 20 02 74	0 °C to +160 °C	100,0	63 mm	G 1/2
K- 07 20 02 75	0 °C to +200 °C	100,0	63 mm	G 1/2
K- 07 20 02 76	-30 °C to +50 °C	100,0	100 mm	G 1/2
K- 07 20 02 77	0 °C to +120 °C	100,0	100 mm	G 1/2
K- 07 20 02 78	0 °C to +160 °C	100,0	100 mm	G 1/2
K- 07 20 02 79	0 °C to +200 °C	100,0	100 mm	G 1/2
K- 07 20 02 80	0 °C to +250 °C	100,0	100 mm	G 1/2
K- 07 20 02 81	-30 °C to +50 °C	100,0	160 mm	G 1/2
K- 07 20 02 82	0 °C to +120 °C	100,0	160 mm	G 1/2
K- 07 20 02 83	0 °C to +200 °C	100,0	160 mm	G 1/2