

K-BIMETALLTHERMOMETER 52-1

Bimetallic thermometers

HANSA FLEX

Karakteristike

| | |
|-------------------|---------------------------|
| Tip | 52 |
| Korekcija prikaza | Trimming pointer |
| Radni tlak | Max. 25 bar (on stem) |
| Uronjivo tijelo | Ø 8 mm, CrNi steel 1.4571 |
| Kućište, prsten | CrNi steel |
| Prozirna pločica | Flat instrument glass |



Napomena

Drugi podatci na zahtjev.

Opis

Applications: Versatile design for use in industrial applications.

Artikli

| Naziv | Područja prikaza | Ø (mm) | Duljina uronjivog tijela | Navoj |
|----------------|------------------|-----------|--------------------------|-------|
| K- 07 20 02 72 | -30 °C to +50 °C | 100,0 | 63 mm | G 1/2 |
| K- 07 20 02 73 | 0 °C to +120 °C | 100,0 | 63 mm | G 1/2 |
| K- 07 20 02 74 | 0 °C to +160 °C | 100,0 | 63 mm | G 1/2 |
| K- 07 20 02 75 | 0 °C to +200 °C | 100,0 | 63 mm | G 1/2 |
| K- 07 20 02 76 | -30 °C to +50 °C | 100,0 | 100 mm | G 1/2 |
| K- 07 20 02 77 | 0 °C to +120 °C | 100,0 | 100 mm | G 1/2 |
| K- 07 20 02 78 | 0 °C to +160 °C | 100,0 | 100 mm | G 1/2 |
| K- 07 20 02 79 | 0 °C to +200 °C | 100,0 | 100 mm | G 1/2 |
| K- 07 20 02 80 | 0 °C to +250 °C | 100,0 | 100 mm | G 1/2 |
| K- 07 20 02 81 | -30 °C to +50 °C | 100,0 | 160 mm | G 1/2 |
| K- 07 20 02 82 | 0 °C to +120 °C | 100,0 | 160 mm | G 1/2 |
| K- 07 20 02 83 | 0 °C to +200 °C | 100,0 | 160 mm | G 1/2 |