

K-DIFFERENZDRUCKMANO Z

Differential pressure gauges with parallel male connector

HANSA FLEX

Karakteristike

Tip	711.12
Izvedba	Bourdon-tube pressure gauge with parallel male connector and two separate measuring systems
Primjena	to measure differential pressures or two different pressures For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Klasa kvalitete	1,6
Temperatura medija	maks. +60 °C
Okolna temperatura	od -20 °C do +60 °C
Kućište, prsten	Steel, black
Materijal mjernog člana i mehanizma brojila s kazaljkom	Legura bakra
Prozirna pločica	Flat instrument glass



Napomena

Drugi podatci na zahtjev.

Artikli

Naziv	Mjerno područje	Ø (mm)	Priključak
K- 07 20 00 55	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 00 56	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 00 57	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 00 58	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 00 59	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 00 60	0 - 10.0 bar	100,0	G 1/2"