

K-MANO

Pressure gauges (CrNi steel type / connection on rear)

HANSA FLEX

Karakteristike

| | |
|--------------------|--|
| Tip | 232.50 |
| Izvedba | Bourdon-tube pressure gauge, CrNi steel type, all-stainless steel |
| Primjena | For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise |
| Klasa kvalitete | 1,6 (Ø 63 mm), 1,0 (Ø 100 mm) |
| Temperatura medija | max. +200 °C |
| Okolna temperatura | -40 °C to +60 °C |
| Kućište | CrNi steel |
| Prozirna pločica | Laminated safety glass Ø 63 = Polycarbonate |



Napomena

Drugi podatci na zahtjev.

Artikli

| Naziv | Mjerno područje | Ø (mm) | Priključak |
|----------------|-----------------|--------|------------|
| K- 07 20 06 10 | -1 / 0.0 bar | 63,0 | G 1/4" |
| K- 07 20 06 11 | 0 - 2.5 bar | 63,0 | G 1/4" |
| K- 07 20 06 12 | 0 - 4.0 bar | 63,0 | G 1/4" |
| K- 07 20 06 13 | 0 - 6.0 bar | 63,0 | G 1/4" |
| K- 07 20 06 14 | 0 - 10.0 bar | 63,0 | G 1/4" |
| K- 07 20 06 15 | 0 - 16.0 bar | 63,0 | G 1/4" |
| K- 07 20 06 16 | 0 - 25.0 bar | 63,0 | G 1/4" |
| K- 07 20 06 17 | 0 - 40.0 bar | 63,0 | G 1/4" |
| K- 07 20 06 18 | 0 - 100.0 bar | 63,0 | G 1/4" |
| K- 07 20 06 19 | 0 - 250.0 bar | 63,0 | G 1/4" |
| K- 07 20 00 53 | 0 - 6.0 bar | 100,0 | G 1/2" |
| K- 07 20 00 54 | 0 - 10.0 bar | 100,0 | G 1/2" |