

K-MANO

Pressure gauges (CrNi steel type / connection on rear)

HANSA FLEX

Karakteristike

Tip	232.50
Izvedba	Bourdon-tube pressure gauge, CrNi steel type, all-stainless steel
Primjena	For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Klasa kvalitete	1,6 (Ø 63 mm), 1,0 (Ø 100 mm)
Temperatura medija	max. +200 °C
Okolna temperatura	-40 °C to +60 °C
Kućište	CrNi steel
Prozirna pločica	Laminated safety glass Ø 63 = Polycarbonate



Napomena

Drugi podatci na zahtjev.

Artikli

Naziv	Mjerno područje	Ø (mm)	Priključak
K- 07 20 06 10	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 06 11	0 - 2.5 bar	63,0	G 1/4"
K- 07 20 06 12	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 06 13	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 06 14	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 06 15	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 06 16	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 06 17	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 06 18	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 06 19	0 - 250.0 bar	63,0	G 1/4"
K- 07 20 00 53	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 00 54	0 - 10.0 bar	100,0	G 1/2"