

K-KFMM U MBAR 10FACH UEBERLASTUNG

Capsule-type pressure gauges for measuring pressure in millibars

HANSA FLEX

Karakteristike

Tip	611.10 (Ø 63), 612.20 (Ø 100)
Izvedba	Capsule-type pressure gauge
Primjena	For gaseous, dry, non-corrosive media
Klasa kvalitete	1,6
Temperatura medija	max. +100 °C
Okolna temperatura	od -20 °C do +60 °C
Kućište	Steel, black (Ø 63 mm)CrNi steel (Ø 100 mm)
Materijal mjernog člana i mehanizma brojila s kazaljkom	Legura bakra
Prozirna pločica	Plexiglass



Napomena

Drugi podatci na zahtjev.

Opis

Overpressure safety 10x FSD, with zero correction

Artikli

Naziv	Mjerno područje	Ø (mm)	Priključak
K- 07 20 06 83	0 - 40 mbar	63,0	G 1/4"
K- 07 20 06 84	0 - 60 mbar	63,0	G 1/4"
K- 07 20 06 85	0 - 100 mbar	63,0	G 1/4"
K- 07 20 06 86	0 - 160 mbar	63,0	G 1/4"
K- 07 20 06 87	0 - 250 mbar	63,0	G 1/4"
K- 07 20 01 08	0 - 40 mbar	100,0	G 1/2"
K- 07 20 01 09	0 - 60 mbar	100,0	G 1/2"
K- 07 20 01 10	0 - 100 mbar	100,0	G 1/2"
K- 07 20 01 11	0 - 160 mbar	100,0	G 1/2"
K- 07 20 01 12	0 - 250 mbar	100,0	G 1/2"