

K-PRMM CHEMIE U

Diaphragm pressure gauges for chemical applications, connection radial on bottom

HANSA FLEX

Karakteristike

| | |
|-------------------------------|---|
| Tip | 422.12 (robust), 432.50 (chemical) |
| Izvedba | Diaphragm pressure gauge in robust design or for chemical applications |
| Primjena | at chemical applications in aggressive environments for gaseous or liquid media, |
| Klasa kvalitete | 1,6 |
| Temperatura medija | max. +100 °C |
| Okolna temperatura | od -20 °C do +60 °C |
| Ø mjerne prirubnice | 100 mm |
| Kućište, prsten | Grey cast iron / CrNi steel, black (robust type), CrNi steel (type for chemical applications) |
| Mjerni član | CrNi steel |
| Prozirna pločica | Flat instrument glass (robust type), Laminated safety glass (type for chemical applications) |
| Mehanizam brojila s kazaljkom | Copper alloy (robust type), CrNi steel (type for chemical applications) |



Napomena

Drugi podatci na zahtjev.

Artikli

| Naziv | Mjerno područje | Ø (mm) | Priključak |
|----------------|-----------------|--------|------------|
| K- 07 20 10 25 | 0 - 6.0 bar | 100,0 | G 1/2" |
| K- 07 20 10 26 | 0 - 10.0 bar | 100,0 | G 1/2" |