


# K-MANO ABSPH MUF DREH MUF

Pressure gauge stopcocks, female - loose (rotatable) female

**HANSA FLEX**

## Karakteristike

|                           |   |
|---------------------------|---|
| <b>Primjena</b>           | For all pressure gauges with a flat gasket acc. to DIN 16258                                    |
| <b>Područje tlaka</b>     | Max. 16 bar, depending on the variant Pressure gauge valves should be used for higher pressures |
| <b>Temperatura</b>        | Max. +50 °C   |
| <b>Kućište</b>            | Brass with a bare metal surface or stainless steel 1.4571                                       |
| <b>Ručka</b>              | Plastic   |
| <b>Ispitna prirubnica</b> | -   |



## Napomena

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B <br>K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B

Drugi podatci na zahtjev.

## Opis

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

## Dodatne informacije

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

## Artikli

| Naziv          | Navoj | PN (bar) | SW (mm) | Materijal |
|----------------|-------|----------|---------|-----------|
| K- 07 20 10 86 | G 1/2 | 25       | 27      | Mjed      |
| K- 07 20 10 87 | G 1/2 | 25       | 27      | Mjed      |