

K-RMM HKR STAHL

Standard pressure gauges with 3-hole bezel, chrome-plated steel, dual scale in bar/psi and clamp fixing, connection on rear

HANSA FLEX

Karakteristike

Tip	111.12
Izvedba	Bourdon-tube pressure gauge, standard design, mounting ring Chromium plated sheet steel Steel chrome plated or black or with triangular bezel
Primjena	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Klasa kvalitete	2,5
Temperatura medija	maks. +60 °C
Okolna temperatura	od -20 °C do +60 °C
Kućište	Sheet steel
Materijal mjernog člana i mehanizma brojila s kazaljkom	Legura bakra
Prozirna pločica	Transparent plastic



Napomena

Drugi podatci na zahtjev.

Artikli

Naziv	Mjerno područje	Ø (mm)	Priključak
K- 07 20 04 04	-1 / 0.0 bar	40,0	G 1/8
K- 07 20 04 05	0 - 1.0 bar	40,0	G 1/8
K- 07 20 04 06	0 - 1.6 bar	40,0	G 1/8
K- 07 20 04 07	0 - 2.5 bar	40,0	G 1/8
K- 07 20 04 08	0 - 4.0 bar	40,0	G 1/8
K- 07 20 04 09	0 - 6.0 bar	40,0	G 1/8
K- 07 20 04 10	0 - 10.0 bar	40,0	G 1/8
K- 07 20 04 11	0 - 16.0 bar	40,0	G 1/8
K- 07 20 04 12	0 - 25.0 bar	40,0	G 1/8