

K-RMM H KUNSTSTOFF

Standard pressure gauges (with plastic housing / connection on rear, central)

HANSA FLEX

Karakteristike

Tip	111.12
Izvedba	Bourdon-tube pressure gauge in standard design
Primjena	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Klasa kvalitete	1,6
Temperatura medija	maks. +60 °C
Okolna temperatura	od -20 °C do +60 °C
Kućište	Plastic
Materijal mjernog člana i mehanizma brojila s kazaljkom	Legura bakra
Prozirna pločica	Transparent plastic



Napomena

Drugi podatci na zahtjev.

Artikli

Naziv	Mjerno područje	Ø (mm)	Priključak
K- 07 20 04 56	-1 / 0.0 bar	40,0	G 1/8
K- 07 20 04 57	0 - 1.6 bar	40,0	G 1/8
K- 07 20 04 58	0 - 2.5 bar	40,0	G 1/8
K- 07 20 04 59	0 - 4.0 bar	40,0	G 1/8
K- 07 20 04 60	0 - 6.0 bar	40,0	G 1/8
K- 07 20 04 61	0 - 10.0 bar	40,0	G 1/8
K- 07 20 04 62	0 - 16.0 bar	40,0	G 1/8
K- 07 20 04 63	0 - 25.0 bar	40,0	G 1/8
K- 07 20 04 64	0 - 40.0 bar	40,0	G 1/8
K- 07 20 05 64	-1 / 0.0 bar	50,0	G 1/4
K- 07 20 05 65	0 - 1.0 bar	50,0	G 1/4
K- 07 20 05 66	0 - 1.6 bar	50,0	G 1/4
K- 07 20 05 67	0 - 2.5 bar	50,0	G 1/4
K- 07 20 05 68	0 - 4.0 bar	50,0	G 1/4
K- 07 20 05 69	0 - 6.0 bar	50,0	G 1/4
K- 07 20 05 70	0 - 10.0 bar	50,0	G 1/4
K- 07 20 05 71	0 - 16.0 bar	50,0	G 1/4
K- 07 20 05 72	0 - 25.0 bar	50,0	G 1/4
K- 07 20 05 73	0 - 40.0 bar	50,0	G 1/4
K- 07 20 05 75	0 - 60.0 bar	50,0	G 1/4
K- 07 20 05 74	0 - 100.0 bar	50,0	G 1/4