

K-RMM U KUNSTSTOFF MZ

Standard pressure gauges, connection radial on bottom

HANSA FLEX

Karakteristike

| | |
|---|---|
| Tip | 111.10 (radial connector on bottom) |
| Izvedba | Bourdon-tube pressure gauge in standard design |
| Primjena | gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise |
| Klasa kvalitete | 1.6 (Art No. K-07200303, K-07403298 - K-07201188: 2.5) |
| Pokazivač | (for Ø 160 mm - red pointer on the scale) red pointer to the window. For measuring ranges 0...0,6 bar bis 0...60 bar |
| Temperatura medija | maks. +60 °C |
| Okolna temperatura | od -20 °C do +60 °C |
| Kućište | Plastic |
| Materijal mjernog člana i mehanizma brojlja s kazaljkom | Legura bakra |
| Prozirna pločica | Transparent plastic |



Napomena

Drugi podatci na zahtjev.

Artikli

| Naziv | Mjerno područje | Ø (mm) | Priključak |
|----------------|------------------|--------|------------|
| K- 07 20 03 03 | -1200 / 0.0 mbar | 100,0 | G 1/2" |
| K- 07 20 03 04 | -1 / 0.0 bar | 100,0 | G 1/2" |
| K- 07 20 03 05 | -1 / +0.6 bar | 100,0 | G 1/2" |
| K- 07 20 03 06 | -1 / +1.5 bar | 100,0 | G 1/2" |
| K- 07 20 03 07 | -1 / +3.0 bar | 100,0 | G 1/2" |
| K- 07 20 03 08 | -1 / +5.0 bar | 100,0 | G 1/2" |
| K- 07 20 03 09 | -1 / +9.0 bar | 100,0 | G 1/2" |
| K- 07 20 02 84 | 0 - 0.6 bar | 100,0 | G 1/2" |
| K- 07 20 02 85 | 0 - 1.0 bar | 100,0 | G 1/2" |
| K- 07 20 02 86 | 0 - 1.6 bar | 100,0 | G 1/2" |
| K- 07 20 02 87 | 0 - 2.5 bar | 100,0 | G 1/2" |
| K- 07 20 02 88 | 0 - 4.0 bar | 100,0 | G 1/2" |
| K- 07 20 02 89 | 0 - 6.0 bar | 100,0 | G 1/2" |
| K- 07 20 02 90 | 0 - 10.0 bar | 100,0 | G 1/2" |
| K- 07 20 02 91 | 0 - 16.0 bar | 100,0 | G 1/2" |
| K- 07 20 02 92 | 0 - 25.0 bar | 100,0 | G 1/2" |
| K- 07 20 02 93 | 0 - 40.0 bar | 100,0 | G 1/2" |
| K- 07 20 11 86 | 0 - 60.0 bar | 100,0 | G 1/2" |
| K- 07 20 11 87 | 0 - 100.0 bar | 100,0 | G 1/2" |
| K- 07 20 11 88 | 0 - 160.0 bar | 100,0 | G 1/2" |