K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

Karakteristike

Radna temperatura	-60 °C to +100 °C (PA 12)
Karakteristike	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Duljina cijevi	3 m
Jedinica ambalaže	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
Materijal	Polyamid PA 12, hard (according to DIN 73378)



Napomena

Operating pressure with 2.5 x overpressure safety!
Drugi podatci na zahtjev.

Opis

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Artikl

Naziv	Vanjski Ø cijevi (mm)	Unutrašnji Ø cijevi (mm)	maks. radni tlak pri 20°C (bar)	Boja
K- 07 10 04 56	12	9	38	plava
K- 07 10 04 58	12	9	38	crna
K- 07 10 04 60	15	12	25	plava
K- 07 10 04 62	15	12	25	crna
K- 07 10 04 64	18	14	28	plava
K- 07 10 04 66	18	14	28	crna
K- 07 10 04 68	22	18	22	plava
K- 07 10 04 70	22	18	22	crna
K- 07 10 04 72	28	23	20	plava
K- 07 10 04 74	28	23	20	crna

Usprkos pažljivoj provjeri ne mogu se isključiti pogreške i zbog toga ne preuzimamo odgovornost za sadržane podatke.