

# K-SPIR SCHL

Spiral hose, without fittings

## Karakteristike

Primjena	Air, gases, oils, greases, fuels, organic and inorganic substances
Radna temperatura	-40 °C to +100 °C



## Napomena

Drugi podatci na zahtjev.

## Opis

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

## Artikli

Naziv	Ø crijeva iznutra (mm)	Ø crijeva izvana (mm)	Ø spirale izvana (mm)	Namoti	Max. working pressure resistance at 23°C (bar)	maks. radna duljina (m)
K- 07 10 07 51	3,1	4,7	38	144	22	10,0
K- 07 10 07 52	4,8	6,3	75	140	16	22,5
K- 07 10 07 53	6,3	7,9	75	135	13	22,5
K- 07 10 07 49	7,9	9,5	115	90	12	22,5
K- 07 10 07 50	9,5	11,8	140	70	11	22,5

## Pribor

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector