

# K-SPIR SCHL DREH VERSCHRAU V

Spiral hose, with swivel adapter and kink protector, braided

**HANSA FLEX**

## Karakteristike

Vrsta priključka with kink protector, swivel type

Radna temperatura -40 °C to +74 °C



## Napomena

Drugi podatci na zahtjev.

## Opis

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

## Artikli

Naziv	Navoj	Ø crijeva iznutra (mm)	Ø crijeva izvana (mm)	Ø vanjskog namota (mm)	Max. working pressure resistance at 23°C (bar)	maks. radna duljina (m)
K- 07 10 07 43	G 1/4	6,3	9,5	42	14	3,0
K- 07 10 07 44	G 1/4	6,3	9,5	42	14	6,0
K- 07 10 07 45	G 1/4	6,3	9,5	42	14	7,5
K- 07 10 07 46	G 3/8	8,0	12,0	55	14	3,0
K- 07 10 07 47	G 3/8	8,0	12,0	55	14	6,0
K- 07 10 07 48	G 3/8	8,0	12,0	55	14	7,5

## Pribor

K-DREHBARE VERSCHRAUBUNG Swivel adapters