

K-VSEH 3-KRAFT

Receptacle combinations »3-Kraft«

HANSA FLEX

Karakteristike

Kućište	Amaplast with hinged cover
Integriran u kućište	Hanging eyelets, wall mounting fixing and standing feet
Izvedba	Pre-wired
Uvodnice voda	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection or grabrails (all introductions to break)
Vrsta zaštite	IP 44



Napomena

Drugi podatci na zahtjev.

Opis

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

Artikli

Naziv	Raspored	Boja
K- 07 10 03 50	3 Schuko socket 16 A 2p + E 230 V	žuta
K- 07 10 03 49	2 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	srebro

Pribor

K-VT 2 KUPPL 7,2 STECKNIP MS	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
K-ZUBEH VSEH 3 KRAFT AIRKRAFT	Accessories for receptacle combinations »3-Kraft« and »airkraft«