

# K-FI MIKRO METALLBEHAELTER MULTIFIX

Micro-filters with metal bowl

**HANSA FLEX**

## Karakteristike

|                              |  |
|------------------------------|--|
| Ulazni tlak                  | Max. 16 bar                                |
| Temperatura medija           | max. 60 °C                                 |
| Okolna temperatura           | Max. 60 °C                                 |
| Finoća filtra                | 0,01 µm                                    |
| Učinkovitost                 | 99.999 %                                   |
| Brtnveni materijal           | NBR  |
| Filtarski uložak             | Borosilicate-POM                           |
| Kućište                      | Die-cast zinc                              |
| Drain valve                  | Semi-automatic                             |
| Mjerenje vrijednosti protoka | FM at P1 = 6 bar and $\Delta p = 0.09$ bar |



## Napomena

\* = Dimensions with adapter plate!

Drugi podatci na zahtjev.

## Opis

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

## Dodatne informacije

on Art. K-07250721: Max. inlet pressure 300 bar. Other cylinder pressure regulators available on request.

## Artikli

| Naziv          | Navoj | Protok (L/min) | A (mm) | B                    | C (mm) | D (mm) | DN | Veličina |
|----------------|-------|----------------|--------|----------------------|--------|--------|----|----------|
| K- 07 25 10 59 | G 1/4 | 280            | 47,8   | 152,5 mm             | 27,0   | 125,5  | 6  | 1        |
| K- 07 25 10 62 | G 1/2 | 720            | 68,8   | 182,7 mm (187,7 mm)* | 72,0   | 149,2  | 15 | 2        |

## Rezervni dijelovi

|                                  |                           |
|----------------------------------|---------------------------|
| K-HALTERBAUSATZ MULTIFIX         | Holder                    |
| K-KOPPELPAKET MEHR               | Coupling packet           |
| K-KOPPELPAKET SCHMA              | Coupling packet           |
| K-AUTOMAT ABLASSVENTIL           | Automatic drain valve     |
| K-PC-BEHAELTER FILTER MULTIFIX   | Polycarbonate tank filter |
| K-METALLBEHAELTER OELER MULTIFIX | Metal tank oiler          |