

# K-VERSCHLUSSNIPPEL IG MS

Self-sealing plugs, brass

**HANSA FLEX**

## Karakteristike

<b>Radni tlak</b>	See table. All values referred to a medium temperature of 50 °C (static working pressure)
<b>Protok zraka</b>	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar)
<b>Temperatura medija</b>	-20 °C to +100 °C
<b>Kućište, čahura, ventil</b>	Brass
<b>Opruga, razorni prsten, kugle</b>	stain less steel
<b>Brtnveni materijal</b>	NBR



## Napomena

Drugi podatci na zahtjev.

## Opis

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

## Artikli

Naziv	Priključak	Nazivni promjer	Radni tlak (bar)	Duljina (mm)	SW (mm)
K- 07 40 10 15	G 1/8 female	4,3	250,0	29,5	14
K- 07 40 10 16	G 1/4 female	6,3	200,0	35,3	19
K- 07 40 10 17	G 3/8 female	7,5	200,0	39,0	22
K- 07 40 10 18	G 1/2 female	11,0	150,0	48,0	27
K- 07 40 10 19	G 3/4 female	13,0	100,0	60,0	36