


K-VERSCHLUSSNIPPEL IG POM

Self-sealing plugs, POM

HANSA FLEX

Karakteristike

Radni tlak	See table. All values referred to a medium temperature of 50 °C (static working pressure)
Protok zraka	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar)
Temperatura medija	-20 °C to +90 °C
Kučiče, čahura	POM (Delrin), white
Ventil	Stainless steel 1.4305
Opruga, razorni prsten, kugle	stain less steel
Brtnveni materijal	NBR



Napomena

Drugi podatci na zahtjev.

Opis

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

Artikli

Naziv	Priključak	Radni tlak (bar)	Duljina (mm)	Nazivni promjer	SW (mm)
K- 07 40 39 58	G 1/8 female	15,0	29,5	4,3	14
K- 07 40 39 59	G 1/4 female	15,0	35,3	6,0	19
K- 07 40 39 60	G 3/8 female	15,0	39,0	7,5	22
K- 07 40 39 61	G 1/2 female	10,0	48,0	11,0	27
K- 07 40 39 62	G 3/4 female	10,0	60,0	13,0	36