


# K-VERSCHLUSSNIPPEL IG POM

Self-sealing plugs, POM

**HANSA FLEX**

## Karakteristike

|                                      |   |
|--------------------------------------|---|
| <b>Radni tlak</b>                    | See table. All values referred to a medium temperature of 50 °C (static working pressure)   |
| <b>Protok zraka</b>                  | 440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar) |
| <b>Temperatura medija</b>            | -20 °C to +90 °C  |
| <b>Kučište, čahura</b>               | POM (Delrin), white   |
| <b>Ventil</b>                        | Stainless steel 1.4305  |
| <b>Opruga, razorni prsten, kugle</b> | stain less steel  |
| <b>Brtveni materijal</b>             | NBR   |



## Napomena

Drugi podatci na zahtjev.

## Opis

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

## Artikli

| Naziv                 | Priključak   | Radni tlak (bar) | Duljina (mm) | Nazivni promjer | SW (mm) |
|-----------------------|--------------|------------------|--------------|-----------------|---------|
| <b>K- 07 40 39 58</b> | G 1/8 female | 15,0             | 29,5         | 4,3             | 14      |
| <b>K- 07 40 39 59</b> | G 1/4 female | 15,0             | 35,3         | 6,0             | 19      |
| <b>K- 07 40 39 60</b> | G 3/8 female | 15,0             | 39,0         | 7,5             | 22      |
| <b>K- 07 40 39 61</b> | G 1/2 female | 10,0             | 48,0         | 11,0            | 27      |
| <b>K- 07 40 39 62</b> | G 3/4 female | 10,0             | 60,0         | 13,0            | 36      |