


# K-VERSCHLUSSNIPPEL IG POM

Self-sealing plugs, POM

**HANSA FLEX**

## Karakteristike

<b>Radni tlak</b>	See table. All values referred to a medium temperature of 50 °C (static working pressure)
<b>Protok zraka</b>	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar)
<b>Temperatura medija</b>	-20 °C to +90 °C
<b>Kučiče, čahura</b>	POM (Delrin), white
<b>Ventil</b>	Stainless steel 1.4305
<b>Opruga, razorni prsten, kugle</b>	stain less steel
<b>Brtveni materijal</b>	NBR



## Napomena

Drugi podatci na zahtjev.

## Opis

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

## Artikli

Naziv	Priključak	Radni tlak (bar)	Duljina (mm)	Nazivni promjer	SW (mm)
K- 07 40 39 58	G 1/8 female	15,0	29,5	4,3	14
K- 07 40 39 59	G 1/4 female	15,0	35,3	6,0	19
K- 07 40 39 60	G 3/8 female	15,0	39,0	7,5	22
K- 07 40 39 61	G 1/2 female	10,0	48,0	11,0	27
K- 07 40 39 62	G 3/4 female	10,0	60,0	13,0	36