
K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

Karakteristike

Radni tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
Protok zraka	560 l/min (at 6 bar and Δp = 0.5 bar)
Temperatura medija	-20 °C to +100 °C
Deblokirajuća čahura	Anodised aluminium
Opruga, razorni prsten, kugle	stain less steel
Brtveni materijal	NBR



Napomena

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.
Drugi podatci na zahtjev.

Opis

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Artikl

Naziv	Priključak	Boja	Duljina (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	zelena	45,0	14
K- 07 35 06 81	G 1/4 male	zelena	47,0	17
K- 07 35 06 82	G 1/8 female	zelena	45,0	14
K- 07 35 06 83	G 1/4 female	zelena	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	plava	45,0	14
K- 07 35 06 89	G 1/4 male	plava	47,0	17
K- 07 35 06 90	G 1/8 female	plava	45,0	14
K- 07 35 06 91	G 1/4 female	plava	47,0	17
K- 07 35 06 92	G 1/8 male	crvena	45,0	14
K- 07 35 06 93	G 1/4 male	crvena	47,0	17
K- 07 35 06 94	G 1/8 female	crvena	45,0	14
K- 07 35 06 95	G 1/4 female	crvena	47,0	17

Usprkos pažljivoj provjeri ne mogu se isključiti pogreške i zbog toga ne preuzimamo odgovornost za sadržane podatke.