

# K-LKS 5 UWB

## Stems and plugs DN 5

### Karakteristike

|                    |   |
|--------------------|---|
| Radni tlak         | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Protok zraka       | 560 l/min (at 6 bar and $\Delta p = 0.5$ bar)               |
| Temperatura medija | -20 °C to +100 °C   |
| Materijal          | Mjed  |



### Napomena

Drugi podatci na zahtjev.

### Artikli

| Naziv          | Definicija        | Boja   | SW (mm) |
|----------------|-------------------|--------|---------|
| K- 07 35 01 54 | Stem, I.D. 6      | zelena | -       |
| K- 07 35 01 55 | Stem, I.D. 6      | Brown  | -       |
| K- 07 35 01 56 | Stem, I.D. 6      | plava  | -       |
| K- 07 35 01 57 | Stem, I.D. 6      | crvena | -       |
| K- 07 35 01 58 | Plug G 1/8 male   | zelena | 17      |
| K- 07 35 01 59 | Plug G 1/4 male   | zelena | 17      |
| K- 07 35 01 60 | Plug G 1/8 female | zelena | 17      |
| K- 07 35 01 61 | Plug G 1/4 female | zelena | 17      |
| K- 07 35 01 62 | Plug G 1/8 male   | Brown  | 17      |
| K- 07 35 01 63 | Plug G 1/4 male   | Brown  | 17      |
| K- 07 35 01 64 | Plug G 1/8 female | Brown  | 17      |
| K- 07 35 01 65 | Plug G 1/4 female | Brown  | 17      |
| K- 07 35 01 66 | Plug G 1/8 male   | plava  | 17      |
| K- 07 35 01 67 | Plug G 1/4 male   | plava  | 17      |
| K- 07 35 01 68 | Plug G 1/8 female | plava  | 17      |
| K- 07 35 01 69 | Plug G 1/4 female | plava  | 17      |
| K- 07 35 01 70 | Plug G 1/8 male   | crvena | 17      |
| K- 07 35 01 71 | Plug G 1/4 male   | crvena | 17      |
| K- 07 35 01 72 | Plug G 1/8 female | crvena | 17      |
| K- 07 35 01 73 | Plug G 1/4 female | crvena | 17      |