
K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

Karakteristike



Radni tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
Protok zraka	1.800 l/min (at 6 bar and Δp = 0.5 bar)
Temperatura medija	-20 °C to +100 °C
Kućište	Brass
Ventil	Die-cast zinc, nickel-plated
Deblokirajuća čahura	Anodised aluminium
Opruga, razorni prsten, kugle	stain less steel
Brtveni materijal	NBR

Napomena

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.
Drugi podatci na zahtjev.

Opis

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Artikl

Naziv	Priključak	Boja	Duljina (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	zelena	57,5	19
K- 07 35 08 02	G 3/8 male	zelena	57,5	19
K- 07 35 08 03	G 1/4 female	zelena	55,5	19
K- 07 35 08 04	G 3/8 female	zelena	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	plava	57,5	19
K- 07 35 08 10	G 3/8 male	plava	57,5	19
K- 07 35 08 11	G 1/4 female	plava	55,5	19
K- 07 35 08 12	G 3/8 female	plava	54,5	19
K- 07 35 08 13	G 1/4 male	crvena	57,5	19
K- 07 35 08 14	G 3/8 male	crvena	57,5	19
K- 07 35 08 15	G 1/4 female	crvena	55,5	19
K- 07 35 08 16	G 3/8 female	crvena	54,5	19

Usprkos pažljivoj provjeri ne mogu se isključiti pogreške i zbog toga ne preuzimamo odgovornost za sadržane podatke.