


K-LKS 7,8 UWB

Stems and plugs DN 7.8

Karakteristike

| | |
|--------------------|---|
| Radni tlak | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Protok zraka | 1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar) |
| Temperatura medija | -20 °C to +100 °C |
| Materijal | Mjed |



Napomena

Drugi podatci na zahtjev.

Artikli

| Naziv | Definicija | Boja | SW (mm) |
|----------------|-----------------|--------|---------|
| K- 07 35 02 71 | Stem, I.D. 6 | zelena | - |
| K- 07 35 02 72 | Stem, I.D. 9 | zelena | - |
| K- 07 35 02 73 | Stem, I.D. 6 | Brown | - |
| K- 07 35 02 74 | Stem, I.D. 9 | Brown | - |
| K- 07 35 02 75 | Stem, I.D. 6 | plava | - |
| K- 07 35 02 76 | Stem, I.D. 9 | plava | - |
| K- 07 35 02 77 | Stem, I.D. 6 | crvena | - |
| K- 07 35 02 78 | Stem, I.D. 9 | crvena | - |
| K- 07 35 02 79 | Plug G 1/4 male | zelena | 17 |
| K- 07 35 02 80 | Plug G 3/8 male | zelena | 19 |
| K- 07 35 02 81 | Plug G 1/4 male | Brown | 17 |
| K- 07 35 02 82 | Plug G 3/8 male | Brown | 19 |
| K- 07 35 02 83 | Plug G 1/4 male | plava | 17 |
| K- 07 35 02 84 | Plug G 3/8 male | plava | 19 |
| K- 07 35 02 85 | Plug G 1/4 male | crvena | 17 |
| K- 07 35 02 86 | Plug G 3/8 male | crvena | 19 |