

K-GRUNDEJEKTION SBP

Basic ejectors

HANSA FLEX

Karakteristike

Karakteristike Vacuum generator without control valves or system monitoring functions, with a high maximum vacuum value (85%)
No moving parts, which means no wear and no maintenance
Maximum suction capacity with minimum compressed air consumption
Minimum size, low weight
For decentralised vacuum generation in highly dynamic processes

Primjena For universal use in lightweight gripper systems to handle air-tight workpieces as well as for automatic separation systems, e.g. in the plastics, electronics and packaging industries.
Also ideal for the construction of ejector blocks for decentralised control of suction pads.


Kućište Plastic (impact-resistant)

Priključak Push-in coupling

Radni tlak 4.5 bar

Stupanj evakuacije 85 %

Prigušivač zvuka Plastic



Napomena

Drugi podatci na zahtjev.

Opis

Purely pneumatic vacuum ejector that operates on the Venturi principle. Compressed air enters the ejector at A and flows through the nozzle B. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet D. This air and the driving air leave the ejector via the silencer C.

Artikli

Naziv	Veličina sapnice	Priključak za komprimirani zrak	Vakuumski priključak	Potrošnja zraka pri usisavanju (L/min)	maks. usisni kapacitet (L/min)	Dimenzije
K- 07 45 01 13	0,5	4 mm	4 mm	14,0	8,0	71mm x 10mm x 28mm
K- 07 45 01 14	0,7	4 mm	4 mm	22,0	16,0	71mm x 10mm x 28mm
K- 07 45 01 15	1,0	6 mm	8 mm	48,0	37,7	97mm x 15mm x 40mm
K- 07 45 01 16	1,5	6 mm	8 mm	105,0	71,0	97mm x 15mm x 40mm
K- 07 45 01 17	2,0	8 mm	10 mm	197,0	127,0	168mm x 20mm x 46mm
K- 07 45 01 18	2,5	8 mm	10 mm	311,0	215,0	168mm x 20mm x 46mm

Pribor

K-GRUNDPLATTEN 1	Base plate
K-ERSATZSCHALLDAEMPFER 3	Replacement silencers
K-ERSATZSCHALLDAEMPFER 1	Replacement silencers