

K-INLINE-EJEKTOREN VR

Inline ejectors »VR«, screw connection

HANSA FLEX

Karakteristike

Karakteristike Vacuum generator with high maximum vacuum level (85% vacuum)
No moving parts, which means no wear and no maintenance
ultra small footprint, suitable for confined spaces
minimal air consumption
low noise

Primjena by screwing / plugging into the distribution beam
direct attachment to the suction pad
for handling various workpieces

Kućište Aluminium eloxed (type VR)

Sustav sapnica Brass (type VR)

Priključak Utični spoj



Napomena

Drugi podatci na zahtjev.

Opis

For vacuum generation directly at the point of use. For direct installation between the suction pad and the compressed air supply. Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector and flows through a nozzle. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet. This air and the driving air leave the ejector and enter the atmosphere via the exhaust air outlet.

Artikl

Naziv	Veličina sapnice	Priključak za ispušni zrak	Priključak za komprimirani zrak	Vakuumski priključak	Stupanj evakuacije	Potrošnja zraka pri usisavanju (L/min)	maks. usisni kapacitet (L/min)	Duljina (mm)	Radni tlak (bar)
K- 07 45 01 29	0,7	M 5 male	G 1/4 IG	G1/8 female	90 %	21,0	14,0	35,0	5,0
K- 07 45 01 30	0,9	M 5 male	G 1/4 IG	G1/8 female	89 %	36,0	21,0	35,0	5,0