

K-INLINE-EJEKTTOREN SLP

Inline ejectors »SLP«, plug connection

Karakteristike

Karakteristike	Vacuum generator with high maximum vacuum level (85% vacuum) No moving parts, which means no wear and no maintenance ultra small footprint, suitable for confined spaces minimal air consumption \nlow noise
Primjena	by screwing / plugging into the distribution beam direct attachment to the suction pad for handling various workpieces
Kućište	plastic (Typ SLP)
Sustav sapnica	Brass (type VR)
Priključak	thread connector





Napomena

Drugi podatci na zahtjev.

Opis

For vacuum generation directly at the point of use. For direct installation between the suction pad and the compressed air supply. Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector and flows through a nozzle. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet. This air and the driving air leave the ejector and enter the atmosphere via the exhaust air outlet.

Artikl

Naziv	Veličina sapnice	Priključak za ispušni zrak	Priključak za komprimirani zrak	Vakuumski priključak	Stupanj evakuacije	Potrošnja zraka pri usisavanju (L/min)	maks. usisni kapacitet (L/min)	Duljina (mm)	Radni tlak (bar)
K- 07 45 01 27	0,5	-	4 mm	4 mm	85 %	13,0	8,0	57,0	4,5
K- 07 45 01 28	0,7	-	4 mm	4 mm	85 %	25,0	16,0	57,0	4,5

Usprkos pažljivoj provjeri ne mogu se isključiti pogreške i zbog toga ne preuzimamo odgovornost za sadržane podatke.