
## K-KOMPAKTEJEKTOREN CP

Compact ejectors »CP«, digital vacuum switch with air-saving function



Karakteristike						
Karakteristike	Vacuum generator with integrated control valves and system monitoring functions Gripping and blowing off can be controlled without the need for external valves Optimised air consumption thanks to many models with differing suction capacities Minimum energy costs in continuous operation thanks to automatic air-saving Easy adjustment with foil keypad and LED display of the settings					
Primjena	Handling of air-tight or slightly porous workpieces in fully automated handling systems e.g. in the robotics, automotive, packaging, electronics, electrical engineering and metalworking industries					
Osnovno tijelo	Anodised aluminium					
Integriran	NC blow-off valve, filter, silencer, non-return valve					
	·					



## Napomena

Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy. Drugi podatci na zahtjev.

## **Opis**

Purely pneumatic vacuum ejector that operates on the Venturi principle. Compressed air enters the ejector at A and flows through the nozzle B. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet D. This air and the driving air leave the ejector via the silencer C.

## Dodatne informacije

Important: Order two connection plugs per ejector. A cable set is included with the compact ejector with automatic air-saving.

Artikl									
Veličina sapnice	Položaj mirovanja usisnog ventila	Priključak za komprimirani zrak	Vakuumski priključak	Potrošnja zraka pri usisavanju (L/min)	maks. usisni kapacitet (L/min)	Dimenzije	Radni tlak <sub>(bar)</sub>		
1,5	NC	G 1/8 IG	G1/8 female	117,0	65,0	72mm x 20mm x 164mm	5,0		
1,5	NO	G 1/8 IG	G1/8 female	117,0	65,0	72mm x 20mm x 164mm	5,0		
2,0	NC	G 1/4 IG	G 3/8 female	190,0	116,0	113mm x 22mm x 168mm	6,0		
2,0	NO	G 1/4 IG	G 3/8 female	190,0	116,0	113mm x 22mm x 168mm	6,0		
2,5	NC	G 1/4 IG	G 3/8 female	310,0	161,0	113mm x 22mm x 183mm	6,0		
2,5	NO	G 1/4 IG	G 3/8 female	310,0	161,0	113mm x 22mm x 183mm	6,0		
	1,5 1,5 2,0 2,0 2,5	sapnice         usisnog ventila           1,5         NC           1,5         NO           2,0         NC           2,0         NO           2,5         NC	sapnice         usisnog ventila         komprimirani zrak           1,5         NC         G 1/8 IG           1,5         NO         G 1/8 IG           2,0         NC         G 1/4 IG           2,0         NO         G 1/4 IG           2,5         NC         G 1/4 IG	sapnice         usisnog ventila         komprimirani zrak         priključak           1,5         NC         G 1/8 IG         G1/8 female           1,5         NO         G 1/8 IG         G1/8 female           2,0         NC         G 1/4 IG         G 3/8 female           2,0         NO         G 1/4 IG         G 3/8 female           2,5         NC         G 1/4 IG         G 3/8 female	sapnice         usisnog ventila         komprimirani zrak         priključak         pri usisavanju (L/min)           1,5         NC         G 1/8 IG         G1/8 female         117,0           1,5         NO         G 1/8 IG         G1/8 female         117,0           2,0         NC         G 1/4 IG         G 3/8 female         190,0           2,0         NO         G 1/4 IG         G 3/8 female         190,0           2,5         NC         G 1/4 IG         G 3/8 female         310,0	sapnice         usisnog ventila         komprimirani zrak         priključak         pri usisavanju (L/min)         kapacitet (L/min)           1,5         NC         G 1/8 IG         G1/8 female         117,0         65,0           1,5         NO         G 1/8 IG         G1/8 female         117,0         65,0           2,0         NC         G 1/4 IG         G 3/8 female         190,0         116,0           2,0         NO         G 1/4 IG         G 3/8 female         190,0         116,0           2,5         NC         G 1/4 IG         G 3/8 female         310,0         161,0	sapnice         usisnog ventila         komprimirani zrak         priključak         pri usisavanju (L/min)         kapacitet (L/min)           1,5         NC         G 1/8 IG         G1/8 female         117,0         65,0         72mm x 20mm x 164mm           1,5         NO         G 1/8 IG         G1/8 female         117,0         65,0         72mm x 20mm x 164mm           2,0         NC         G 1/4 IG         G 3/8 female         190,0         116,0         113mm x 22mm x 168mm           2,0         NO         G 1/4 IG         G 3/8 female         190,0         116,0         113mm x 22mm x 168mm           2,5         NC         G 1/4 IG         G 3/8 female         310,0         161,0         113mm x 22mm x 183mm		

Pribor			
K-ANSCH KABEL VAKUUMSCHAL	Connection cable for vacuum switch		
K-ERSATZSCHALLDAEMPFER 2	Replacement silencers		
K-ERSATZFILTERELEMENTE	Replacement filter element		

11.12.2025 HANSA-FLEX AG www.hansa-flex.com