# K-FEDERSTOESSEL
Spring plungers

## Karakteristike

| | |
|---|---|
| **Primjena** | Handling of workpieces with differing heights (eg. Curved metal sheets)<br>Handling of very sensitive workpieces, very soft landing is assured |
| **Temperatura min.** | 0 °C |
| **Temperatura max.** | 80 °C |
| **Priključak usisavača** | M 3 female |
| **Izvedba** | Spring plunger with high-strength steel rodl, guide sleeve and lower damping spring<br>Plunger rod with integrated vacuum guide |
| **Put opruge** | 5,0 mm |



## Napomena

Drugi podatci na zahtjev.

## Opis

Suitable for all round or oval suction pads in our standard range.

## Artikl

| Naziv | Vakuumski priključak | Duljina (mm) | Okomito opterećenje (N/m2) |
|---|---|---|---|
| **K- 07 45 00 73** | M 3 female | 33,5 | 550 |
| **K- 07 45 00 76** | M 5 female | 41,2 | 1500 |
| **K- 07 45 00 74** | M 5 female | 47,2 | 1500 |
| **K- 07 45 00 75** | M 5 female | 59,2 | 1500 |
| **K- 07 45 00 70** | G 1/8 female | 80,0 | 3700 |
| **K- 07 45 00 67** | G 1/8 female | 95,0 | 3700 |
| **K- 07 45 00 71** | G 1/8 female | 93,0 | 3700 |
| **K- 07 45 00 68** | G 1/8 female | 124,5 | 2400 |
| **K- 07 45 00 72** | G 1/8 female | 124,0 | 2400 |
| **K- 07 45 00 69** | G 1/8 female | 154,0 | 2400 |

*Usprkos pažljivoj provjeri ne mogu se isključiti pogreške i zbog toga ne preuzimamo odgovornost za sadržane podatke.*