

# K-SAUGPLATTENAUFHAENGUNG


Flexible suction pad mountings

**HANSA FLEX**

## Karakteristike

**Primjena** For handling of workpieces with sloping using large-area vacuum gripper  
Handling of large plates that can sag when lifting  
In combination with spring plungers to compensate height-differences and Unevenness

**Posebna obilježja** very good adaptation to oblique workpiece surfaces  
automatic Rückstellung in die Ausgangslage  
vacuum-tight design with integrated protection against damage



## Napomena

Drugi podatci na zahtjev.

## Opis

Flexible suction pad mounting. By flexing in all directions, this mounting allows the suction pad to better adapt itself to sloping workpieces.

## Artikl

Naziv	Unutarnji navoj 1	Vanjski navoj 2	H	Materijal	L1	L2	Kut W	Okomito opterećenje	Moment savijanja	SW
			(mm)		(mm)	(mm)	(°)	(N/m <sup>2</sup> )	(N/m <sup>2</sup> )	(mm)
K- 07 45 01 47	G 1/4	M 10 x 1.25	27,0	Steel, rubber	10,5	8,0	12	500	8,0	17
K- 07 45 01 48	G 1/4	G 1/4	27,0	Steel, rubber	12,0	12,0	12	750	10,0	17