K-WV 3/2 5/2 NAMUR

3/2 and 5/2-way spool valves

Karakteristike

Mediji	Air, neutral gases (filtered)
Diferencijalni tlak	2 - 10 bar
dopušten statički tlak	Max. 10 bar
Radna temperatura	-25 °C to +60 °C
Električni priključak	Connector socket Pg 9P, 3 x DIN 46244 / VDE 0580
Kućište	Aluminium, anodised black
Brtveni materijal	NBR and PUR



Napomena

Drugi podatci na zahtjev.

Opis

Pilot-operated 3/2 and 5/2-way spool valves with threaded port connections and a NAMUR style interface. The two conversion plates supplied with each valve allow the device to be adapted to a 3/2-way or 5/2-way function. The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure. Includes a manual operator as standard.

Artikl

Naziv	Napon	Port 1	Priključak 3 + 5	DN	Protok (L/min)
K- 07 15 00 01	230 V, 50 Hz	G 1/4	G 1/8	6	700
K- 07 15 00 02	24 V DC	G 1/4	G 1/8	6	700

Usprkos pažljivoj provjeri ne mogu se isključiti pogreške i zbog toga ne preuzimamo odgovornost za sadržane podatke.