

# K-DRS MDR 5 O ENTLASTU VENT

»MDR 5« pressure switches, without unloading valve / on/off switch / motor protection circuit, with flange 1/4

**HANSA FLEX**

## Karakteristike

Temperatura medija	-5 °C to +80 °C
maks. tlak isključenja	16 bar
Uklopni kapacitet	5,5 kW
Vrsta kontakta	NC (3-pole)
maks. učestalost uklapanja	120 (electrical), 600 (mechanical)
Vrsta zaštite	IP 54



## Napomena

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)  
Drugi podatci na zahtjev.

## Opis

Three-phase version

## Napomene uz narudžbu

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

## Dodatne informacije

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

## Artikl

Naziv	Priključak za komprimirani zrak	Područje namještanja
K- 07 30 24 24	G 1/2	2,0 - 11,0 bar
K- 07 30 24 26	G 1/2	2,5 - 16,0 bar