

K-DRS MDR 5 O ENLASTU VENT

»MDR 5« pressure switches, without unloading valve / on/off switch / motor protection circuit, with flange 1/4

HANSA FLEX

Karakteristike

| | |
|----------------------------|------------------------------------|
| Temperatura medija | -5 °C to +80 °C |
| maks. tlak isključenja | 16 bar |
| Uklopni kapacitet | 5,5 kW |
| Vrsta kontakta | NC (3-pole) |
| maks. učestalost uklapanja | 120 (electrical), 600 (mechanical) |
| Vrsta zaštite | IP 54 |



Napomena

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Drugi podatci na zahtjev.

Opis

Three-phase version

Napomene uz narudžbu

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Dodatne informacije

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

Artikl

| Naziv | Priklučak za komprimirani zrak | Područje namještanja |
|----------------|--------------------------------|----------------------|
| K- 07 30 24 24 | G 1/2 | 2,0 - 11,0 bar |
| K- 07 30 24 26 | G 1/2 | 2,5 - 16,0 bar |