

# K-DRS WECHSELKONTAKT

Pressure switches, changeover type

**HANSA FLEX**

## Karakteristike

<b>Izvedba</b>	Spring-loaded diaphragm (NBR); Spring-loaded piston (10 to 70 bar versions)
<b>Područje primjene</b>	Air, hydraulic oil, oil emulsions, water
<b>Okolna temperatura</b>	-25 °C to +85 °C
<b>Električni priključak</b>	Tab connectors 3 x 6.3 x 0.8
<b>Učestalost uklapanja</b>	200/min.
<b>Uklopni napon</b>	42 V
<b>Funkcija</b>	Changeover
<b>Materijal</b>	Galvanised steel



## Napomena

Drugi podatci na zahtjev.

## Opis

For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

## Artikli

Naziv	Navoj	Područje namještanja	Materijal
K- 07 30 28 33	G 1/4	0,3 - 2,0 bar	Galvanised steel
K- 07 30 28 34	G 1/4	1,0 - 10,0 bar	Galvanised steel
K- 07 30 28 35	G 1/4	10,0 - 70,0 bar	Galvanised steel