

# K-DRS W BAJONETT

Pressure switches - changeover type

## Karakteristike

Izvedba	Spring-loaded diaphragm (UR); Spring-loaded piston; (10 to 70 bar versions)
Okolna temperatura	-25 °C to +85 °C
Električni priključak	Bayonet coupling connector Ø 2.5 mm
Učestalost uklapanja	200/min.
Dimenzionirani napon	42 V
Funkcija	Changeover
Materijal	Galvanised steel



## Napomena

Drugi podatci na zahtjev.

## Opis

Special pressure switches for critical (water) or outdoor applications. Maximum degree of protection IP67 when a bayonet coupling is used for the electrical connection.

## Artikli

Naziv	Navoj	Područje namještanja
K- 07 30 28 36	G 1/8	0,5 - 2,0 bar
K- 07 30 28 37	G 1/8	1,0 - 10,0 bar
K- 07 30 28 38	G 1/8	10,0 - 70,0 bar
K- 07 30 28 39	G 1/4	0,5 - 2,0 bar
K- 07 30 28 40	G 1/4	1,0 - 10,0 bar
K- 07 30 28 41	G 1/4	10,0 - 70,0 bar

## Pribor

**K-WECHSELKONTAKT BANJOETT** Changeover type bayonet coupling