

K-DRS W DREHBAR

Pressure switches, changeover type, turnable

HANSA FLEX

Karakteristike

| | |
|-----------------------|--|
| Izvedba | Spring-loaded diaphragm (NBR) |
| Područje primjene | Air, hydraulic oil, oil emulsions, water |
| Okolna temperatura | -25 °C to +85 °C |
| Električni priključak | Coupling plug Pg 9, DIN 43650 |
| Učestalost uklapanja | 200/min. |
| Dimenzionirani napon | 250 V |
| Funkcija | Changeover |
| Materijal | Galvanised steel |



Napomena

Drugi podatci na zahtjev.

Opis

For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

Artikli

| Naziv | Navoj | Područje namještanja |
|----------------|-------|----------------------|
| K- 07 30 28 55 | G 1/8 | 0,3 - 2,0 bar |
| K- 07 30 28 56 | G 1/8 | 1,0 - 10,0 bar |
| K- 07 30 28 57 | G 1/8 | 10,0 - 70,0 bar |
| K- 07 30 28 58 | G 1/4 | 0,3 - 2,0 bar |
| K- 07 30 28 59 | G 1/4 | 1,0 - 10,0 bar |
| K- 07 30 28 60 | G 1/4 | 10,0 - 70,0 bar |