K-BKR LEICHT IG IG

Ball valves, lightweight type, female/female thread

Karakteristike

Područje primjene	Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture
Radni tlak	Max. 40 bar
Radna temperatura	-15 °C to +90 °C
Opis navoja	G thread acc. DIN EN ISO 228-1
Kućište	Nickel-plated brass
Poluga	Alu, painted black
Kugla	Nickel-plated brass
Brtva kugle	PTFE
Brtva vretena	HNBR / EPDM / PTFE. 2 O-Rings (HNBR / EPDM) 1 gasket (PTFE) additional PTFE-gasket





Napomena

Drugi podatci na zahtjev.

Artikl

Naziv	DN	Navoj	A (mm)	B (mm)	L (mm)
K- 07 30 00 33	8	G 1/4	85,0	42,0	39,0
K- 07 30 00 34	10	G 3/8	85,0	42,0	43,0
K- 07 30 00 35	15	G 1/2	85,0	46,0	50,0
K- 07 30 00 36	20	G 3/4	105,0	53,0	58,0
K- 07 30 00 37	25	G 1	105,0	57,0	69,0
K- 07 30 00 38	32	G 1 1/4	130,0	70,0	81,0
K- 07 30 00 39	40	G 1 1/2	130,0	76,0	93,0
K- 07 30 00 40	50	G 2	165,0	92,0	110,0

Usprkos pažljivoj provjeri ne mogu se isključiti pogreške i zbog toga ne preuzimamo odgovornost za sadržane podatke.