

# K-3 BKR L EINFACHWIRKEND

Stainless steel ball valves, 3-way, with single-acting actuator, L-bore

**HANSA FLEX**

## Karakteristike

|                                |  |
|--------------------------------|--|
| <b>Izvedba</b>                 | Pneumatic actuators, in double- or single acting version, with integrated end-position feedback                                |
| <b>Provrt</b>                  | L oblik  |
| <b>Radni tlak</b>              | max. 63 bar (depending on temperature and nominal size)  |
| <b>Radna temperatura</b>       | -20 °C to +70 °C   |
| <b>Zakretni kut</b>            | 90 °   |
| <b>Normirana sučelja</b>       | Interface actuator / valve: four or eight threaded holes in the drive housing according to EN ISO 5211, Interface actuator / S |
| <b>Upravljački tlak</b>        | 5.5 bar  |
| <b>Ventilski adapter</b>       | Acc. to NAMUR  |
| <b>Pogon</b>                   | aluminium eloxed   |
| <b>Brtva pogona</b>            | NBR  |
| <b>Kuglasti ventil</b>         | Stainless steel 1.4401, with ISO-flange plate  |
| <b>Brtva kuglastog ventila</b> | PTFE/FKM   |



## Napomena

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Drugi podatci na zahtjev.

## Opis

3-way cock, reduced bore

## Dodatne informacije

Other T-positions on request

## Artikli

| Naziv          | DN | Navoj    | Položaj | A<br>(mm) | B<br>(mm) | D<br>(mm) | L<br>(mm) | SW<br>(mm) |
|----------------|----|----------|---------|-----------|-----------|-----------|-----------|------------|
| K- 07 30 03 11 | 15 | Rp 1/2   | L 1     | 133,0     | 139,0     | 20,0      | 73,0      | 27         |
| K- 07 30 03 12 | 20 | Rp 3/4   | L 1     | 137,0     | 159,0     | 23,0      | 80,0      | 32         |
| K- 07 30 03 13 | 25 | Rp 1     | L 1     | 161,0     | 174,5     | 28,5      | 90,0      | 41         |
| K- 07 30 03 14 | 32 | Rp 1 1/4 | L 1     | 161,0     | 179,5     | 36,5      | 90,0      | 50         |
| K- 07 30 03 15 | 40 | Rp 1 1/2 | L 1     | 180,0     | 185,0     | 37,0      | 105,0     | 55         |
| K- 07 30 03 16 | 50 | Rp 2     | L 1     | 209,0     | 213,5     | 47,5      | 115,0     | 71         |