


K-T-STUECKE IG IG AG 2 2

Tees, female-female-male

HANSA FLEX

Karakteristike

| | |
|-------------------|---------------------------------|
| Radni tlak | 60 bar |
| Radna temperatura | Max. 150 °C |
| Unutarnji navoj | Parallel to DIN EN ISO 228-1 |
| Materijal | Brass with a bare metal surface |
| Vanjski navoj | conical acc. DIN 2999 |



Napomena

Drugi podatci na zahtjev.

Artikl

| Naziv | Navoj | L1 (mm) | L2 (mm) | SW (veličina ključa) |
|----------------|---------|------------|------------|----------------------|
| K- 07 40 11 70 | G/R 1/8 | 39,5 | 21,0 | 10 mm |
| K- 07 40 11 71 | G/R 1/4 | 49,0 | 23,5 | 13 mm |
| K- 07 40 11 72 | G/R 3/8 | 54,0 | 28,0 | 17 mm |
| K- 07 40 11 73 | G/R 1/2 | 64,5 | 33,5 | 21 mm |
| K- 07 40 11 74 | G/R 3/4 | 69,5 | 36,5 | 25 mm |
| K- 07 40 11 75 | G/R 1 | 84,0 | 45,0 | 30 mm |