

# K-T-STUECKE IG 1 2

Tees, female-female-female

**HANSA FLEX**

## Karakteristike

|                   |                              |
|-------------------|------------------------------|
| Radni tlak        | 60 bar                       |
| Radna temperatura | Max. 150 °C                  |
| Unutarnji navoj   | Parallel to DIN EN ISO 228-1 |
| Materijal         | poniklani mjed               |



## Napomena

Drugi podatci na zahtjev.

## Artikli

| Naziv          | Navoj | L1<br>(mm) | L2<br>(mm) | SW (veličina ključa) |
|----------------|-------|------------|------------|----------------------|
| K- 07 40 48 92 | M 5   | 22,0       | 11,0       | 9 mm                 |
| K- 07 40 11 04 | G 1/8 | 42,0       | 21,0       | 10 mm                |
| K- 07 40 11 05 | G 1/4 | 51,0       | 25,5       | 13 mm                |
| K- 07 40 11 06 | G 3/8 | 56,0       | 28,0       | 17 mm                |
| K- 07 40 11 07 | G 1/2 | 67,0       | 33,5       | 21 mm                |
| K- 07 40 11 14 | G 3/4 | 73,0       | 36,5       | 25 mm                |
| K- 07 40 11 15 | G 1   | 90,0       | 45,0       | 30 mm                |