

K-T-STUECKE IG AG IG 2

Tees, female-male-female

HANSA FLEX

Karakteristike

| | |
|-------------------|------------------------------|
| Radni tlak | 60 bar |
| Radna temperatura | Max. 150 °C |
| Unutarnji navoj | Parallel to DIN EN ISO 228-1 |
| Materijal | poniklani mjed |
| Vanjski navoj | conical acc. DIN 2999 |



Napomena

Drugi podatci na zahtjev.

Artikl

| Naziv | Navoj | L1 (mm) | L2 (mm) | SW (veličina ključa) |
|----------------|---------|------------|------------|----------------------|
| K- 07 40 48 93 | M 5 | 22,0 | 11,5 | 9 mm |
| K- 07 40 11 08 | G/R 1/8 | 42,0 | 18,5 | 10 mm |
| K- 07 40 11 09 | G/R 1/4 | 51,0 | 23,5 | 13 mm |
| K- 07 40 11 10 | G/R 3/8 | 56,0 | 26,0 | 17 mm |
| K- 07 40 11 11 | G/R 1/2 | 67,0 | 31,0 | 21 mm |
| K- 07 40 11 12 | G/R 3/4 | 73,0 | 33,0 | 25 mm |
| K- 07 40 11 13 | G/R 1 | 90,0 | 39,0 | 30 mm |