

K-RD MUFFE RUND

Reducing sockets, round

HANSA FLEX

Karakteristike

| | |
|-----------------|------------------------------|
| Radni tlak | Max. 20 bar |
| Unutarnji navoj | Parallel to DIN EN ISO 228-1 |
| Materijal | Stainless steel 1.4408 |



Napomena

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes. Drugi podatki na zahtjev.

Artikli

| Naziv | Unutarnji navoj 1 | Unutarnji navoj 2 | L1 (mm) |
|----------------|-------------------|-------------------|------------|
| K- 07 40 14 73 | G 1/4 | G 1/8 | 27,0 |
| K- 07 40 14 74 | G 3/8 | G 1/8 | 28,4 |
| K- 07 40 14 75 | G 3/8 | G 1/4 | 29,5 |
| K- 07 40 45 80 | G 1/2 | G 1/8 | 32,0 |
| K- 07 40 14 76 | G 1/2 | G 1/4 | 32,0 |
| K- 07 40 14 77 | G 1/2 | G 3/8 | 33,5 |
| K- 07 40 14 78 | G 3/4 | G 3/8 | 36,0 |
| K- 07 40 14 79 | G 3/4 | G 1/2 | 38,5 |
| K- 07 40 45 81 | G 1 | G 3/8 | 38,8 |
| K- 07 40 14 80 | G 1 | G 1/2 | 40,5 |
| K- 07 40 14 81 | G 1 | G 3/4 | 41,5 |
| K- 07 40 45 82 | G 1 1/4 | G 1/2 | 43,5 |
| K- 07 40 14 82 | G 1 1/4 | G 3/4 | 45,0 |
| K- 07 40 14 83 | G 1 1/4 | G 1 | 48,0 |
| K- 07 40 45 83 | G 1 1/2 | G 3/4 | 47,5 |
| K- 07 40 14 84 | G 1 1/2 | G 1 | 54,1 |
| K- 07 40 14 85 | G 1 1/2 | G 1 1/4 | 54,0 |
| K- 07 40 14 86 | G 2 | G 1 | 54,0 |
| K- 07 40 45 84 | G 2 | G 1 1/4 | 57,0 |
| K- 07 40 14 87 | G 2 | G 1 1/2 | 56,0 |