

K-KM

Hexagonal lock nuts

Karakteristike

| | |
|-----------------|------------------------------|
| Radni tlak | Max. 20 bar |
| Unutarnji navoj | Parallel to DIN EN ISO 228-1 |
| Materijal | Stainless steel 1.4408 |



Napomena

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.
Drugi podatci na zahtjev.

Artikli

| Naziv | Navoj | L1 (mm) | SW (veličina ključa) |
|----------------|---------|------------|----------------------|
| K- 07 40 38 78 | G 1/8 | 6,2 | 14 mm |
| K- 07 40 38 79 | G 1/4 | 7,2 | 22 mm |
| K- 07 40 38 80 | G 3/8 | 8,0 | 27 mm |
| K- 07 40 38 81 | G 1/2 | 9,5 | 32 mm |
| K- 07 40 38 82 | G 3/4 | 9,8 | 36 mm |
| K- 07 40 38 83 | G 1 | 10,4 | 46 mm |
| K- 07 40 38 84 | G 1 1/4 | 11,0 | 55 mm |
| K- 07 40 38 85 | G 1 1/2 | 12,3 | 60 mm |
| K- 07 40 38 86 | G 2 | 13,0 | 74 mm |